

1. ČELIČNA UŽAD I LANCI Wire ropes and chains


1.2. Opća namjena

Čelično uže: 6x37 + čelična jezgra

Wire rope: 6x37 + IWRC

2.1 2.2 3.1 BL

Promjer (mm)	Min. prekidna sila (kN) 1770 N/mm ²	Min. prekidna sila (kN) 1960 N/mm ²	Težina (kg/m)
Diameter	MBL	MBL	Weight
4.50	11.4	12.7	0.077
5.00	14.1	15.6	0.095
6.00	20.3	22.5	0.13
7.00	27.6	30.6	0.18
8.00	36.1	40.0	0.24
9.00	45.7	50.6	0.30
10.00	56.4	62.5	0.38
11.00	68.2	75.5	0.46
12.00	81.2	89.9	0.54
13.00	95.2	105.4	0.64
14.00	110	122	0.74
15.00	127	141	0.86
16.00	144	159	0.97
17.00	164	182	1.10
18.00	183	203	1.23
19.00	204	226	1.37
20.00	225	249	1.52
21.00	249	276	1.68
22.00	273	302	1.84
23.00	299	331	2.01
24.00	325	360	2.19
25.00	353	391	2.38
26.00	381	422	2.57
27.00	412	456	2.77
28.00	442	489	2.98
30.00	510	565	3.44



- EN 12385-4
- DIN 3066
- završna obrada: crno, el. galvanizirano ili vruće cinčano
- čvrstoća žice: 1770 N/mm² ili 1960 N/mm²




Čelično uže: 6x24 + vlaknasta jezgra

Wire rope: 6x24+ FC

2.1 2.2 3.1 BL

Promjer (mm)	Min. prekidna sila (kN) 1570 N/mm ²	Težina (kg/100 m)
Diameter	MBL	Weight
10	44.9	31.4
12	64.0	45.2
14	88.0	61.5
16	115.0	80.4
18	145.0	102
20	180.0	126
22	217.0	152
24	259.0	181
26	30.4	212
28	352.0	246



- EN 12385-4
- uže za lashing
- DIN 3068
- završna obrada: crno, el. galvanizirano ili vruće cinčano
- čvrstoća žice: 1570 N/mm²