

1. ČELIČNA UŽAD I LANCI Wire ropes and chains


1.2. Opća namjena

Čelično užje: 6x36WS+čelična jezgra

Wire rope: 6x36WS+ IWRC

2.1 2.2 3.1 BL

Promjer (mm)	Min. prekidna sila (kN) 1960 N/mm ²	Min. prekidna sila (kN) 2160 N/mm ²	Težina (kg/100 m)
Diameter	MBL	MBL	Weight
6	25	28	15
8	45	49	26
9	57	62	33
10	70	77	41
11	84	93	49
12	100	111	59
13	118	130	69
14	137	151	80
15	157	173	92
16	179	197	105
17	202	222	118
18	226	249	133
19	252	278	148
20	279	308	164
21	308	339	180
22	338	372	198
23	369	407	216
24	402	443	236
25	436	481	256
26	472	520	276
27	509	561	298
28	547	603	321
29	587	647	344
30	628	692	368
32	715	787	419
34	807	889	473
36	904	997	530
38	1008	1110	591
40	1116	1230	654
42	1231	1356	721
44	1351	1489	792
46	1476	1627	865
48	1608	1772	942
50	1744	1922	1023
52	1887	2079	1106
54	2035	2242	1193
56	2188	2411	1283
58	2347	2587	1376
60	2512	2768	1472
62	2682	2956	1572
66	3039	3350	1782
70	3419	3768	2004



- EN 12385-4
- DIN 3064
- završna obrada: crno, el. galvanizirano ili vruće cinčano
- čvrstoća žice: 1960 N/mm² ili 2160 N/mm²

