


# LANAC

## LANAC DIN 766

### LANAC G30 DIN 766



1. Prirodna boja
2. Elektro cinčano
3. Vruće cinčano
4. Inox AISI 304/AISI 316.

Šifra	Dimenzija		Unutarnja dužina			Vanjska dužina	Vanjska širina		Dužina			Težina
	(d)		(P)			(w1)	(w2)		11 karika			
	MM	±MM	MM	+MM	-MM	MM	MM	MM	+MM	-MM	KG/m	
18219	2	0.2	12	0.2	0.2	3.5	7.5	132	1.0	0.5	0.07	
18220	3	0.2	16	0.2	0.2	4.2	11	176	1.4	0.7	0.16	
18221	4	0.2	16	0.3	0.2	5	13.7	176	2.1	1.1	0.32	
18222	5	0.2	18.5	0.4	0.2	6	17	203.5	2.4	1.2	0.5	
18223	6	0.2	18.5	0.4	0.2	7.2	20.2	203.5	2.4	1.2	0.8	
18224	7	0.3	22	0.4	0.2	8.4	23.8	242	3.0	1.4	1.1	
18225	8	0.3	24	0.4	0.2	9.6	27.2	264	3.2	1.5	1.4	
18226	9	0.4	27	0.5	0.3	10.8	30.6	297	3.6	1.8	1.8	
18227	10	0.4	28	0.5	0.3	12	34	308	3.7	1.9	2.2	
18228	11	0.4	31	0.5	0.3	13.2	37.4	341	4.0	2.0	2.7	
18229	12	0.3	36	0.6	0.3	14.4	40.8	396	4.4	2.2	3.10	
18230	13	0.5	36	0.6	0.3	15.6	44.2	396	4.6	2.4	3.8	
18231	14	0.6	41	0.7	0.4	16.8	47.6	451	5.4	2.7	4.4	
18232	16	0.6	45	0.8	0.4	19.2	54.4	495	6.0	3.0	5.7	
18233	18	0.9	50	0.8	0.4	21.6	61.2	550	6.6	3.3	7.3	
18234	19	0.4	53	0.9	0.4	22.8	64.6	583	7.0	3.7	7.97	
18235	20	1.0	56	1.0	0.5	24.0	68.0	616	7.4	3.7	9.0	
18236	22	1.2	62	1.1	0.5	26.4	75.0	682	8.0	4.0	11.0	
18237	23	1.2	64	1.1	0.5	27.6	78.2	704	8.4	4.2	12	
18238	26	1.3	73	1.2	0.6	31.2	88.4	803	9.6	4.8	15	
18239	28	1.4	78	1.3	0.65	33.8	95.2	858	10.2	5.1	18	
18240	30	1.5	84	1.4	0.7	41.0	102	924	11.0	5.5	19.5	
18241	32	1.6	90	1.5	0.75	43.0	108.8	990	11.8	5.9	23.0	