








POLIESTERSKE PRIVEZNICE

POLIESTERSKE BESKONAČNE PRIVEZNICE



- Sve poliesterske beskonačne priveznice imaju faktor sigurnosti 7:1 i proizvedene su prema Europskoj normi DIN-EN 1492-2
- Boja poliesterske priveznice je kod za nosivost (različita boja-različita nosivost)
- Proizvedene su od 100% visokokvalitetnog poliester.
- Svaka poliesterska priveznica ima ušivenu deklaraciju na kojoj je navedena nosivost, faktor sigurnosti i način sigurne upotrebe priveznice.
- Moguća je isporuke različitih priveznica većih nosivosti.

GURTNE

Nosivost Boja	Nosivost poliesterskih priveznice pod različitim kutevima (t)						
	100%	80%	200%	140%	100%	70%	50%
				 0~45°	 45~60°	 0~45°	 45~60°
	1.0	0.8	2.0	1.4	1.0	0.7	0.5
1t	1,000	800	2,000	1,400	1,000	700	500
2t	2,000	1,600	4,000	2,800	2,000	1,400	1,000
3t	3,000	2,400	6,000	4,200	3,000	2,100	1,500
4t	4,000	3,200	8,000	5,600	4,000	2,800	2,000
5t	5,000	4,000	10,000	7,000	5,000	3,500	2,500
6t	6,000	4,800	12,000	8,400	6,000	4,200	3,000
8t	8,000	6,400	16,000	11,200	8,000	5,600	4,000
10t	10,000	8,000	20,000	14,000	10,000	7,000	5,000
15t	12,000	9,600	24,000	16,800	12,000	8,400	6,000
20t	15,000	12,000	30,000	21,000	15,000	10,500	7,500
25t	20,000	16,000	40,000	28,000	20,000	14,000	10,000