


5. DIZALICE, KOLICA I HVATALJKE Hoists, clamps

5.2. Hvataljke

Hvataljka horizontalna tip PPD RX-lift

Horizontal lifter type PPD RX-lift

Nosivost u paru (t)	Otvor hvataljke (mm)	A (mm)	B (mm)	C (mm)	D (mm)	Neto težina (kg)
Pair capacity	Jaw opening					Net weight
0,8	0-25	22	125	165	40	2,5
1	0-30	25	148	205	40	3,5
1,6	0-30	30	148	205	45	4,0
2,0	0-40	30	172	245	47	5,0
3,2	0-45	30	180	245	50	6,0
4,0	0-50	30	170	260	52	6,5
5,0	0-55	30	180	260	56	7,5
6,0	0-65	37	210	308	62	10,5
6,0 BT	0-130	37	316	310	62	22
8,0	0-100	55	282	400	65	22
10,0	0-125	55	325	500	75	33




2.1 2.2 CE

- EN 13155
- horizontalno dizanje i transport čeličnih ploča i konstrukcija u horizontalnom položaju
- ne bočno opterećivati
- ne koristiti u 2, 3 i 4-krakim priveznicama bez nosive grede/jarma
- ne koristiti za dizanje materijala čija tvrdća prelazi HRC30

Hvataljka horizontalna tip THK RX-lift

Horizontal lifter type THK RX-lift

Nosivost u paru (t)	Otvor hvataljke (mm)	T (mm)	U (mm)	V (mm)	L (mm)	Neto težina (kg)
Pair capacity	Jaw opening					Net weight
0,5 THKS	0-35	165	60	43	25	3,1
1,0 THKS	0-60	180	80	68	25	6,0
1,5 THKS	0-60	180	80	68	25	6,5
2,0 THKS	0-60	180	80	68	25	7,5
3,0 THKS	0-60	220	90	80	30	10
4,0 THKS	0-60	220	90	70	30	11,5
5,0 THKS	0-60	220	110	74	30	15,5
10 THKS	0-60	220	130	78	40	23
1,0 THK	0-100	180	80	120	25	7
1,5 THK	0-100	180	80	120	25	7,5
2,0 THK	0-100	180	80	120	30	9,5
3,0 THK	0-100	220	90	120	30	12
4,0 THK	0-100	220	90	120	30	14,50
5,0 THK	0-100	220	110	123	45	20,0
10,0 THK	0-100	220	125	120	45	28,0




2.1 2.2 CE

- EN 13155
- horizontalno dizanje i transport u parovima, ili više parova ili sa 3 hvataljke u transportu čeličnih ploča horizontalno
- ne koristiti u 2, 3 i 4-krakim priveznicama izuzev 2-krakih kada se koristi u paru sa podiznom gredom/jaram sa hvataljkama na krajevima
- ne bočno opterećivati
- ne koristiti sa 4-krakim priveznicama, u tom (koristiti jaram sa 2-krakim priveznicama na krajevima)

Hvataljka horizontalna tip HPC RX-lift

Horizontal lifter type HPC RX-lift

Nosivost u paru (t)	Otvor hvataljke (mm)	B (mm)	C (mm)	D (mm)	E (mm)	Neto težina (kg)
Pair capacity	Jaw opening					Net weight
1,5	0-50	210	130	100	30	4,3
3,0	0-50	236	203	110	36	6,0
5,0	0-60	273	251	130	40	12,0
9,0	0-100	380	290	165	40	28,4



2.1 2.2 CE

- EN 13155
- horizontalno dizanje i transport čeličnih ploča i konstrukcija
- ne prekoračivati kut od 60° pri dizanju

- ne dizati nehrđajući čelik ili bakar
- koristiti na temperaturama manjim od 100°C