

1. ČELIČNA UŽAD I LANCI Wire ropes and chains


1.8. Spiralno uže

Spiralno uže: 1×7

Spiral rope: 1x7

Promjer (mm)	Min. prekidna sila (kN) 1770 N/mm ²	Težina (kg/100m)
Diameter	MBL	Weight
1,0	0,96	0,5
1,5	2,11	1,10
2,0	3,75	1,96
2,5	5,86	3,1
3,0	8,44	4,4
3,5	11,5	6,0
4,0	15,0	7,8
4,5	19,0	9,9
5,0	23,5	12,2
6,0	33,8	17,6

CE 2.1 2.2 3.1 BL




- EN 12385-10
- DIN 3052
- završna obrada: cinčano
- čvrstoća žice: 1770 N/mm²

Spiralno uže: 1×19

Spiral rope: 1x19

Promjer (mm)	Min. prekidna sila (kN) 1770 N/mm ²	Težina (kg/100m)
Diameter	MBL	Weight
1,5	2,09	1,09
2,0	3,72	1,94
2,5	5,82	3,0
3,0	8,38	4,4
4,0	14,9	7,8
5,0	23,3	12,1
6,0	33,5	17,5
7,0	45,6	23,8
8,0	59,6	31,0

CE 2.1 2.2 3.1 BL




- EN 12385-10
- DIN 3053
- završna obrada: cinčano
- čvrstoća žice: 1770 N/mm²

Spiralno uže: 1×37

Spiral rope: 1x37

Promjer (mm)	Min. prekidna sila (kN) 1770 N/mm ²	Težina (kg/100m)
Diameter	MBL	Weight
3,0	8,17	4,3
4,0	14,5	7,7
5,0	22,7	12,1
6,0	32,7	17,4
7,0	44,5	23,7
8,0	58,1	30,9
6,0	33,5	17,5
7,0	45,6	23,8
8,0	59,6	31,0

CE 2.1 2.2 3.1 BL



- EN 12385-10
- DIN 3054
- završna obrada: cinčano
- čvrstoća žice: 1770 N/mm²