

3. SPOJNI PRIBOR General hardware

3.5. Natezni vijci, zateznice

Green Pin zateznica G-6313

Green Pin® Turnbuckle G-6313

2.1 2.2 CE 3.1 MTCa



Nosivost (t)	Promjer oka vilice (mm)	Max. duljina produljenja vilice (inch)	A (mm)	H (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Težina (kg/kom)
WLL	Diameter jaw eye	take up									Weight
2.36	41	6	3/4	16	369	487	439	24	38	16	2.59
2.36	41	9	3/4	16	444	640	514	24	38	16	3.13
2.36	41	12	3/4	16	520	792	590	24	38	16	3.42
2.36	41	18	3/4	16	670	1,096	740	24	38	16	4.51
3.27	48	12	7/8	19	561	826	638	27	42	19	4.93
3.27	48	18	7/8	19	713	1,132	790	27	42	19	6.41
4.5	54	24	1 1/4	20	903	1,470	988	31	50	22	8.9
4.54	54	6	1	20	447	554	532	31	50	22	5.18
4.54	54	12	1	20	598	859	683	31	50	22	6.43
4.54	54	18	1	20	750	1,168	835	31	50	22	8.4
6.9	68	12	1 1/4	26	641	914	748	44	71	29	11.2
6.9	68	18	1 1/4	26	803	1,228	910	44	71	29	13.6
6.9	68	24	1 1/2	26	962	1,539	1,069	44	71	29	15
9.71	80	12	1 1/2	28	675	942	806	52	71	35	17
9.71	80	18	1 1/2	28	825	1,244	956	52	71	35	19.3
9.71	80	24	1 1/2	28	980	1,551	1,111	52	71	35	20.7
12.7	90	18	1 3/4	33	938	1,316	1,092	60	86	41	25
12.7	90	24	1 3/4	33	1,089	1,621	1,243	60	86	41	28.7
16.8	107	24	2	40	1,151	1,671	1,338	63	93	51	45.4
27.2	143	24	2 1/2	41	1,255	1,831	1,480	75	114	57	88
34	158		2 3/4	41	1,348	1,882	1,604	90	110	70	98

