


Zaštita PVC za poliesterske priveznice

Protection sleeves PVC for polyester slings

Zaštita PVC je proizvod koji je namijenjen za korištenje u kombinaciji s trakastim priveznicama prema EN 1492-1 i beskonačnim priveznicama prema EN 1492-2. Svrha zaštite od PVC navlake je produžiti vijek trajanja priveznice i zaštititi priveznicu i teret kojim se rukuje tijekom operacija dizanja ili rukovanja. Točnije, koristi se u sljedeće svrhe:

PVC protection sleeve is product that is intended to be used in combination with webbing slings acc. to EN 1492-1 and round slings acc. to EN 1492-2. The purpose of a PVC sleeve protection is to extend the service life of the sling and to protect both the sling and the load being handled during lifting or handling operations. Specifically, it is used for the following purposes:

- **Mehanička zaštita**
 zaštita PVC štiti priveznicu od mehaničkog trošenja, kao što je trenje od oštih rubova, kutova, abrazivnih površina itd. Smanjuje rizik od posjekotina, ogrebotina ili uboda.
the PVC sleeve protects the sling against mechanical wear, such as friction from sharp edges, corners, abrasive surfaces, etc. It reduces the risk of cuts, scratches or punctures.
- **Zaštita od vlage i kemikalija**
 PVC je otporan na vodu, ulja, masti, otapala i druge kemikalije, čime se sprječava propadanje tekstilnog materijala priveznice.
PVC is resistant to water, oils, greases, solvents, and other chemicals, helping prevent the degradation of the sling's textile material.
- **Kontrolirano klizanje i jednostavno pozicioniranje**
 zaštita PVC omogućuje priveznici da glatko klizi po površini tereta, što može olakšati pozicioniranje priveznice tijekom operacija dizanja.
the PVC sleeve allows the sling to slide more smoothly over the surface of the load, which can make positioning the sling easier during lifting operations.
- **Zaštita površine tereta**
 osim zaštite priveznice, zaštita PVC također može zaštititi površinu tereta koji se podiže, sprječavajući nastanak tragova, ogrebotina ili oštećenja na teretu.
in addition to protecting the sling, the PVC protection sleeve can also protect the surface of the lifted object, preventing marks, scratches, or damage.



Tehnički parametri i dimenzije:

Technical Parameters & Dimensions:

Materijal Material	Širina Width	Debljina Thickness	Za trakaste priveznice prema EN 1492-1 For Webbing Sling acc. to EN 1492-1	Za beskonačne priveznice prema EN 1492-2 For Round Sling acc. to EN 1492-2
PVC	65 mm	2 mm	1,0 t - 2,0 t	1,0 t - 3,0 t
PVC	85 mm	2 mm	1,0 t - 2,0 t	1,0 t - 6,0 t
PVC	120 mm	2 mm	1,0 t - 4,0 t	1,0 t - 8,0 t

